

Warren-Morrisson valves Ltd
Standard Packing\Preservation Types

Prior to the despatch of any products, all goods are identified, inspected and cleaned.

Depending on the destination and transportation types also consequently determines the necessary degree of packing and preservation required, unless of course specified.

Packing\Dunnage comprises:

Bubble wrapping.

Plastic cut sheeting.

Corrugated plied cardboard inserts.

Shredded card\papers.

Polystyrene chips (not advisable for packing sensitive electrical equipment).

Condensed foam.

Nylon end capping for flange protection and prevention of possible ingress.

Moisture absorbent lining.

Preservation comprises:

Industrial corrugated cardboard cartons.

Industrial corrugated cardboard cartons wood lined flooring.

Various pallet and bespoke platform sizes with encapsulating shrink-wrapping and nylon tensioned strapping.

Wooden case production for heavy items upto 700 kgs gross

Close boarded constructed cases. (treated/untreated/certified)

Boarding: 19 mm thickness 150 mm width .

Vertical battens to transmit stacking loads: 19 mm thickness 75 mm minimum width.

Rigidity: internal diagonal bracing applied where necessary.

Battens: cross braces applied to prevent movement of contents.

Skids: fitted to allow use of forklift: 100 mm minimum width and ground clearance of at the very least 75 mm.

All wooden cases and platforms are assembled using a pneumatically operated nailing gun. Nail Length: 60 mm

Environment: *The recycling of dunnage\ packing materials is encouraged where it is deemed suitable for use.*

All services and materials supplying our logistics operation are selected from our ASL, operating and strictly conforming in accordance with ISO: 9001:2000